

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Rábalux

**Supplier's address:** Magyarország - Rábalux Világítástechnika Zrt., Körtefa 5., 9027 Győr, HU

**Model identifier:** 3935

## Type of light source:

|                                                     |     |                                 |      |
|-----------------------------------------------------|-----|---------------------------------|------|
| Lighting technology used:                           | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | LED |                                 |      |
| Mains or non-mains:                                 | MLS | Connected light source (CLS):   | Yes  |
| Colour-tuneable light source:                       | Yes | Envelope:                       | -    |
| High luminance light source:                        | No  |                                 |      |
| Anti-glare shield:                                  | Yes | Dimmable:                       | No   |

## Product parameters

| Parameter                                                                                                                                      | Value                  | Parameter                                                                                                                                                  | Value                              |
|------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| <b>General product parameters:</b>                                                                                                             |                        |                                                                                                                                                            |                                    |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                  | 16                     | Energy efficiency class                                                                                                                                    | G                                  |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 1 150 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3000...6500                        |
| On-mode power ( $P_{on}$ ), expressed in W                                                                                                     | 16,0                   | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal                                                                               | 0,00                               |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal                                                | 0,00                   | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 83                                 |
| Outer dimensions without                                                                                                                       | Height                 | 90                                                                                                                                                         | Spectral power distribution in the |
|                                                                                                                                                | Width                  | 300                                                                                                                                                        |                                    |
|                                                                                                                                                | Depth                  | 300                                                                                                                                                        |                                    |
|                                                                                                                                                |                        |                                                                                                                                                            | See image in last page             |

|                                                                                                                         |                    |                                       |                                      |  |
|-------------------------------------------------------------------------------------------------------------------------|--------------------|---------------------------------------|--------------------------------------|--|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)                       |                    |                                       | range 250 nm to 800 nm, at full-load |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | Yes                | If yes, equivalent power (W)          | 80                                   |  |
|                                                                                                                         |                    | Chromaticity coordinates (x and y)    | 0,321<br>0,346                       |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |                    |                                       |                                      |  |
| R9 colour rendering index value                                                                                         | 4                  | Survival factor                       | 0,90                                 |  |
| the lumen maintenance factor                                                                                            | 0,90               |                                       |                                      |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |                    |                                       |                                      |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,90               | Colour consistency in McAdam ellipses | 6                                    |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | Yes <sup>(b)</sup> | If yes then replacement claim (W)     | 16                                   |  |
| Flicker metric (Pst LM)                                                                                                 | 0,7                | Stroboscopic effect metric (SVM)      | 0,3                                  |  |

(a) : not applicable;

(b) : not applicable;

