## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Rábalux

Supplier's address: Magyarország - Rábalux Világítástechnika Zrt., Körtefa 5., 9027 Győr, HU

## Model identifier: 71058

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS			
Light source cap-type	LED					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						

Parameter		Value	Parameter	Value		
General product parameters:						
•.	nption in on- 00 h), rounded st integer	6	Energy efficiency class	G		
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	230 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	3 000		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	6,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
(P <sub>net</sub> ) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	130	Spectral power dis-	See image		
sions without	Width	250	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	150	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordi- nates (x and y)	0,442 0,401
Parameters for directional light s	ources:		
Peak luminous intensity (cd)	-	Beam angle in de- grees, or the range of beam angles that can be set	
Parameters for LED and OLED lig	ht sources:		
R9 colour rendering index value	-3	Survival factor	1,00
the lumen maintenance factor	0,96		

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

